RROCESSING COPY



INFORMATION REPORT INFORMATION REPORT

CENTRAL INTELLIGENCE AGENCY

				.972	गन्नदाः			
-				·				
TRY Hu	ingary	•			REPORT			
				D-44 (1)	nical DATE DISTR		PR 1957	ţ.
CT C	mbine r	near Pétfü	rdő R.	Peti Chem	pical _DATE DISTR becalton NO. PAGES	3 , U P	ארו וארו	25X1
			1/9					
					REQUIREMEN NO.	NT RD		
					REFERENCES	:		
OF					KLI EKLIACES	•		
& ACQ								į
ACQ	SOL	IRCE EVALUA	TIONS ARE	DEFINITIVE	APPRAISAL OF CON	ITENT IS TE	NTATIVE	
						<u> </u>		4
si	tuated	near Pétfi	Brd8 (47-	re -09 N: 18-	port on the Pét 07 E). The rep	chemics	l combine	,
ti	on on t	he layout	(sketch)	and the	working process	of the p	olant.	ma-
	<i>?</i>					-		6 1 8
_	<u>`</u>		· · · · · · · ·					i.
							*	e Ĉ
								4
·		•						25 X 1
·	· · · · · · · · · · · · · · · · · · ·	•			· · · · · · · · · · · · · · · · · · ·			25X1
	•	`			· · · · · · · · · · · · · · · · · · ·			25X1
	:	•						25X1
	:							25X1
	:							25X1
	:							25X1
		· .						25X1
								25X1
								25X1
								25X1
								25X1
								25X1
	Alexander of the second of the							25X1
	Action on the same of the same							25X1
	Action on the Company of the Company							25X1
	April on the control of the control							25X1
	Action with the second of the			SECR	ET			25X1

INFORMATION REPORT INFORMATION REPORT

25X1

SECRFT

25X1

GECRET

HUNGARY

Economic

PETI CHE ICAL COLBINE, Near PETFURDO.

- 1. This combine utilizes the oil from the NAGY LENGYEL Field. Its object is to obtain high grade fuels from Hungarian oil. The oil has four volatiles and Bitumen content of $1l_{5/2}$, sulphur 3/2.
- 2. The crude oil from NAGY HENGYED is taken into the Filot Plant. A carbon powder impregnated with a ferrous compound is used on the oil in the fluid phase with a suspended catalyst. H₂ gas is added at a temperature of 400° C. at a pressure of 100 atmospheres. The substance then passes to reactor, separator and cooling towers. The catalyst and asphaltenes are eliminated. The residue passes to a Hydrodesulphurization reactor with hydrogen over a catalyst bed at 70 atmospheres and 350° C. The next step would be the catalytic cracking into higher fractions. This has not yet been done practically, and therefore no information on the eventual capacity of the plant could be given.
- 3. A plan of the layout of this combine is attached.

CECRET. 25X1

